



ITEM	QTY	PART NAME	A-2097 W/STAINLESS STEEL TRIM	
			MATERIAL	PART NUMBER
1	1	TOP GUIDE	STEEL W/SS INSERT	29-1-XS
2	1	STEM	STAINLESS STEEL	29-2-SS
3	1	RETAINER	STEEL, PLATED (3)	29-3-CS
4	1	BODY	STEEL	29-4-CS
5	1	SPRING	ALLOY STEEL, PLATED (3)	29-5-AS
6	1	FOLLOWER	STEEL, PLATED (3)	29-6-CS
7	2	WIRE SEAL	SS/LEAD	22-72-PB
8	1	TOP LOCKNUT	STEEL, PLATED (3)	23-8-CS
9	1	WASHER	NEOPRENE (1)	23-9-NE
10	1	SEAT "O" RING	BUNA-N (1)	29-10-BN
11	1	STEM "O" RING	BUNA-N (1)	29-11-BN
12	1	ADJUSTMENT NUT	STEEL, PLATED (3)	23-12-CS
13	1	LOCKNUT	STEEL, PLATED (3)	23-13-CS
14A	2	STUD	ALLOY, STEEL	23-14-AS
14B	2	STUD	ALLOY, STEEL	23-141-AS
15	4	NUT	STEEL, PLATED (3)	10-15-CS
16	1	NAMEPLATE	STAINLESS STEEL	29-16-SS
17	1	GASKET (2)	COMP. ASB. (1)	27-17-AB
18	2	DRIVE SCREWS	STAINLESS STEEL	763-11-SS

**NOTES:**

- (1) ALTERNATE MATERIALS AVAILABLE.
- (2) NOT FURNISHED UNLESS REQUESTED.
- (3) STANDARD PLATING FOR GENERAL SERVICE IS ZINC OR CADMIUM. PLATING CAN BE CHANGED OR ELIMINATED PER CUSTOMER'S SPECIFICATIONS.

VALVE PART NO.	PRESS. SETTING (PSIG)	FLOW RATE (SCFM AIR)
A-2097	75	21,602

NET FLOW AREA: 16.36 SQUARE INCHES  
WEIGHT OF VALVE: 85 LBS.  
FLOW RATED @ 85 PSIG

AAR PRD122006